

| Pos.Nr. | Description   | Amount | Unit price | Total |
|---------|---|--------|------------|-------|
|         | <p><b>Automatic check valves DN200 (181)</b></p> <p><b>Brand:</b> MwStop® check valves -<br/>For supplementary assembly in rainwater drains</p> <p><b>Material:</b><br/>Housing - stainless steel EN 1.4404</p> <p>Check valve membrane - NBR: sealing material consists of suitable material for sewage and rainwater</p> <p>The installation takes place from the shaft in the finished rainwater drain</p> <p>Installation in rainwater drain with an inside diameter of DN 200 (181)</p> <p>Assembly / fastening:<br/>The attachment is carried out using a mounting bracket or a mounting flange welded to the stainless steel tube using stainless screws, which must be adequately dimensioned according to the back pressure.</p> <p><b>Backflow level:</b><br/>5 meters (Standard)<br/>3 meters (Soft)</p> <p><b>Opening pressure:</b><br/>approx. 9,05 cm</p> <p><b>Proof of delivery:</b><br/>Proof of delivery from the manufacturer or a certified MwStop-dealer must be enclosed.</p> <p><b>Manufacturer:</b><br/>MTA-Water Products GmbH<br/>Handelsstrasse 16, A-9300 St.Veit/Glan<br/>Tel:+43 4212 71491 Fax:+43 4212 72298<br/><a href="mailto:office@mta-messtechnik.at">office@mta-messtechnik.at</a></p> |        |            |       |